

## Grain bins of XE series

### Overall sizes and capacity

Bin model	Height, m	Diameter, mm	Geometric volume, m <sup>3</sup>	Operational volume, m <sup>3</sup>	Diameter of entry hole from the compressor, mm	Diameter of entry hole for the flour, mm	Diameter of discharge hole, mm	Pressure of the air, supplied to the dome-breaker system, Mpa	Air consumption for dome-breaking, m <sup>3</sup> /min	Weight, kg
XE-160A	12,144	2652	52,9	50,0	40	75	500	0,08 - 0,1	3	3160
XE-160A-01	11,644	2652	50,5	47,3	40	75	500	0,08 - 0,2	3	3037
XE-160A-02	11,144	2652	48,1	44,9	40	75	500	0,08 - 0,3	3	2914
XE-160A-03	10,644	2652	45,7	42,4	40	75	500	0,08 - 0,4	3	2791
XE-160A-04	10,144	2652	43,3	40,0	40	75	500	0,08 - 0,5	3	2667
XE-160A-05	9,644	2652	40,9	37,6	40	75	500	0,08 - 0,6	3	2544
XE-160A-06	9,144	2652	38,5	35,2	40	75	500	0,08 - 0,7	3	2421
XE-160A-07	8,644	2652	36,1	32,8	40	75	500	0,08 - 0,8	3	2297
XE-160A-08	8,144	2652	33,7	30,4	40	75	500	0,08 - 0,9	3	2174
XE-160A-09	7,644	2652	31,3	28,0	40	75	500	0,08 - 0,10	3	2051
XE-160A-10	7,144	2652	28,9	25,6	40	75	500	0,08 - 0,11	3	1927
XE-160A-11	6,644	2652	26,5	23,2	40	75	500	0,08 - 0,12	3	1804
XE-160A-12	6,144	2652	24,1	20,8	40	75	500	0,08 - 0,13	3	1681
XE-160A-13	5,644	2652	21,7	18,4	40	75	500	0,08 - 0,14	3	1558
XE-160A-14	5,144	2652	19,3	16,0	40	75	500	0,08 - 0,15	3	1434
XE-160A-15	4,644	2652	16,9	13,6	40	75	500	0,08 - 0,16	3	1311